

Acrylonitrile Butadiene Styrene ABS black



Thermoformed materials processed on RECYTHERM:

- thermoformed packaging
- coils
- skeletons
- automotive trays





Treatment process: Grinding Ground material size: 10 mm

SPECIFICATIONS

PROPERTY	VALUE	METHOD	
Color	White / Black	-	
Moisture	Less than 2%	Dessiccateur test at 110°/10min	
MFI (220°/10kg)	Between 8 and 13	ISO 1133	
Hot density	Between 0.82 and 0.98	ISO 1133	

Please note that the information above is derived from average values of different batches.

We perform regular and continuous sampling to ensure representativeness throughout the height of the Q-Bag.

Due to the nature of the raw materials, these values may vary. It is the customer's responsibility to optimize processing conditions and ensure suitability for use in their own products. It is also recommended that the material be pre-dried before use.











TRACEABILITY

Precise composition tracking

- ✓ Each Q-bag of raw material is associated with a detailed composition profile
- ✓ Our information system allows us to know precisely the proportions and types of plastics present in each batch

Transparency on material origin

- √ The origin of each waste entering the composition of the ground material is rigorously documented.
- ✓ This traceability ensures the quality and compliance of our recycled materials

Real-time information capture

- ✓ As soon as waste is received at our site, the information is instantly integrated into our database.
- ✓ The use of barcodes ensures fast and reliable data entry, eliminating the risk of errors or information loss

PACKAGING

CONSUMABLES	CHARACTERISTICS		
Wooden pallets	1m x 1m		
Q-bag	101cm x 101cm x 150cm (Material PP)	All our Q-BAGS are	
Stretch film	CAST 150 % 500mmx1380mlX 23µ	covered and wrapped	
Covers PEBD	124/2x57x254cm	on a custom pallet	
Density Q-bag (weight)	Between 700kg and 1100kg		

IDENTIFICATION





